



SPM International limited - Unit 4 - Houndhill Park - Bolton Road  
Wath-upon-Deerne - Rotherham - South Yorkshire - S63 7JY  
Tel: +44 (0) 1709 871111 - Fax: +44 (0) 1709 871122

Registered in England N° 3615543 - Registered Office: 3 Cloth Street - Barbican - London EC1A 7NP



## Product descriptions

Technical information are downloadable from our website [www.spm-international.com](http://www.spm-international.com)



Impact 200



Impact 120



Impact 60

[www.spm-international.com](http://www.spm-international.com)

Surface protection and handrails

# Impact



## 200/120/60 height wall protection rails- fixing on rail

### Specification

- Description: curved wall protection system made of smooth PVC (Impact 200/120 or 60 as manufactured by SPM). PVC rails project 30 mm, are 200/120 or 60 mm deep and snap-fix to continuous pre-drilled aluminium core. 3 mm thick, Class 0 fire-rated and solid colour, the PVC rails provide a smooth surface finish with decorative grooves. Finish is provided by end pieces, external and internal 90° smooth PVC angle pieces and aluminium joint blocks.
- Colour: selected by architects from manufacturer's standard range.
- Installation sequence: recommended height of protection rail centreline 0.80 m above floor level for mid-level wall protection or above plinth for low level wall protection. Snap-fixes to continuous pre-drilled aluminium core.